


活动法兰式热电偶 Movable flange type thermocouple

型 号 Model	分度号 Graduation	测温范围 °C Range of temperature measurement °C	热响应时间 Thermal response time	保护管材质 Material for protective tube	规格 Specification		
					d	L	
WRM-330 WRM ₂ -330	N	0~800	<90s	1Cr18Ni9Ti	Φ16	150 200 250 300 350 400 500 750 1000 1500 2000 2150	
		0~1100		0Cr25Ni20			
		WRM-330G WRM ₂ -330G	0~800	<24s			1Cr18Ni9Ti
		0~1100	0Cr25Ni20				
WRN-330 WRN ₂ -330	K	0~800	<90s	1Cr18Ni9Ti			
		0~1100		0Cr25Ni20			
		WRN-330G WRN ₂ -330G	0~800	<24s			1Cr18Ni9Ti
		0~1100	0Cr25Ni20				
WRE-330 WRE ₂ -330	E	0~800	<90s	1Cr18Ni9Ti			Φ20
WRE-330G WRE ₂ -330G							
WRC-330 WRC ₂ -330	T	0~350	<90s	1Cr18Ni9Ti			
WRC-330G WRC ₂ -330G							
WRF-330 WRF ₂ -330	J	0~600	<90s	1Cr18Ni9Ti			
WRF-330G WRF ₂ -330G					<24s		
WRM-331 WRM ₂ -331	N	0~800	<90s	1Cr18Ni9Ti			
		0~1100		0Cr25Ni20			
		WRM-331G WRM ₂ -331G	0~800	<24s	1Cr18Ni9Ti		
		0~1100	0Cr25Ni20				
WRN-331 WRN ₂ -331	K	0~800	<120s	1Cr18Ni9Ti			
		0~1100		0Cr25Ni20			
		WRN-331G WRN ₂ -331G	0~800	<24s	1Cr18Ni9Ti		
		0~1100	0Cr25Ni20				
WRE-331 WRE ₂ -231	E	0~800	<120s	1Cr18Ni9Ti			
WRE-331G WRE ₂ -231G					<24s		
WRC-331 WRC ₂ -231	T	0~350	<120s	1Cr18Ni9Ti			
WRC-331G WRC ₂ -231G					<24s		
WRF-331 WRF ₂ -231	J	0~600	<120s	1Cr18Ni9Ti			
WRF-331G WRF ₂ -231G					<24s		



防水式330 331



防水式3300 3310

- 1) 型号330、331为防水式，防护等级IP55;
 - 2) 型号320、321为防喷式，防护等级IP65，其它参数同330、331;
 - 3) 保护管其余材质根据协议订货。
- 1) Model 330 and 331 are waterproof type type with the protective grade being IP55.
- 2) Model 320 and 321 are anti-spraying type with the waterproof grade being IP65. the other parameters are the same as model 130 and 131.
- 3) The other material for protective tubes are ordered according to the agreement.

