

固定螺纹锥式热电偶 Fixed thread cone thermocouple

型号 Model	分度号 Graduation	测温范围 °C Range of temperature measurement °C	热响应时间 Thermal response time	保护管材质 Material for protective tube	规格 Specification	
					d	L
WRM-620 WRM <sub>2</sub> -620	N	0~800	<90s	1Cr18Ni9Ti	φ15	300×150 350×200 400×250 450×300 500×350 550×400 650×500
		0~1100		0Cr25Ni20		
WRM-620G WRM <sub>2</sub> -620G	N	0~800		1Cr18Ni9Ti		
		0~1100		0Cr25Ni20		
WRN-620 WRN <sub>2</sub> -620	K	0~800		1Cr18Ni9Ti		
		0~1100		0Cr25Ni20		
WRN-620G WRN <sub>2</sub> -620G	K	0~800		1Cr18Ni9Ti		
		0~1100		0Cr25Ni20		
WRE-620 WRE <sub>2</sub> -620	E	0~800		1Cr18Ni9Ti		
WRC-620 WRC <sub>2</sub> -620	T	0~350		1Cr18Ni9Ti		
WRF-620 WRF <sub>2</sub> -620	J	0~600	1Cr18Ni9Ti			
				WRF-620G WRF <sub>2</sub> -620G	J	0~600
WRM-630 WRM <sub>2</sub> -630	N	0~800	1Cr18Ni9Ti			
		WRM-630G WRM <sub>2</sub> -630G	N	0~1100	0Cr25Ni20	
WRM-630 WRM <sub>2</sub> -630	N			0~800	1Cr18Ni9Ti	
		WRM-630G WRM <sub>2</sub> -630G	N	0~1100	0Cr25Ni20	
WRN-630 WRN <sub>2</sub> -630	K			0~800	1Cr18Ni9Ti	
		WRN-630G WRN <sub>2</sub> -630G	K	0~1100	0Cr25Ni20	
WRN-630 WRN <sub>2</sub> -630	K			0~800	1Cr18Ni9Ti	
		WRN-630G WRN <sub>2</sub> -630G	K	0~1100	0Cr25Ni20	
WRE-630 WRE <sub>2</sub> -630	E			0~800	1Cr18Ni9Ti	
		WRE-630G WRE <sub>2</sub> -630G	E			0~800
WRC-630 WRC <sub>2</sub> -630	T			0~350	1Cr18Ni9Ti	
		WRC-630G WRC <sub>2</sub> -630G	T			0~350
WRF-630 WRF <sub>2</sub> -630	J			0~600	1Cr18Ni9Ti	
		WRF-630G WRF <sub>2</sub> -630G	J			0~600

- 1) 型号620、620G为防喷式，防护等级IP65；型号630、630G为防水式，防护等级IP55；
- 2) 保护管其余材质根据协议订货；
- 3) 公称压力为≤15MPa。

- 1) Model 620 and 620G are anti-spraying type with the protective grade being IP65; Model 630 and 630G are waterproof type type with the protective grade being IP55;
- 2) The material for the rest protective tube is ordered according to the agreement.
- 3) Nominal pressure is: ≤15MPa.

型号示例 Examples of models	螺纹规格 Thread specification	
	代号 Code	M
WRN-620	-	M33×2
WRN-620	A	NPT1
WRN-630	-	M33×2
WRN-630	A	NPT1



